

JELL CHEMICALS, INC.

9353 Seymour Ave. Schiller Park, IL 60176

800/747-5355

MATERIAL SAFETY DATA SHEET

Report Date: 1/19/00

Page 1 of

EMERGENCY PHONE #: 1-800-535-5053

Section I - Product Identification

Product Class: Blend

Product Code I.D.: JCI-150

Trade Name: Anco EZ100

Section II A - Hazardous Ingredients

The precise composition of this mixture is considered proprietary information. A complete disclosure will be provided to a physician or nurse in the event of a medical emergency. None of the components in this mixture are listed as a carcinogen per IARAC, NTP, OSHA.

Section II B - Occupational Exposure Limits (Y=Yes, N=No, N/E= Not Established)

No.	(OSHA)PEL/TWA	PEL/CEILING
1	100.000ppm	N/E
2	100.000ppm	N/E

No.	(OSHA)PEL/STEL	Skin*
1	150.000ppm	N
2	150.000ppm	Y

No.	(ACGIH)TLV/TWA	TLV/Ceiling
1	100.000ppm	N/E
2	100.000ppm	N/E

No.	(ACGIH)TLV/STEL	Skin*
1	150.000ppm	N
2	150.000ppm	Y

*(Skin) Absorption may contribute to the overall exposure to this material. Take appropriate measures to prevent skin contact..

Section III - Physical Data

Boiling point: 243 Degrees F(Represents boiling point of lowest boiling material)

Evaporation: <1(ether=1)

Vapor Density: >1(air=1)

% solid: 0.56(theoretical)

Weight per gallon: 7.88(theoretical)

V.O.C. lbs gallon: 7.88(theoretical)

JELL CHEMICALS INC.

Material Safety Data Sheet-Anco EZ100

Report Date: 1/19/00

Page 2 of 3

Section IV - Health Information

EYE CONTACT: Based on the presence of component 2 product is presumed to be moderately irritating to the eyes. Based on the presence of component 1 product vapors and/or mists may also be irritating to the eyes.

SKIN CONTACT: Exposure may produce skin irritation. Based on the presence of component 1 absorption through the skin may result in symptoms of exposure as those described for inhalation and ingestion.

INHALATION: Exposure May Produce irritation to the nose, throat, respiratory tract, and other mucous membranes. Based on the presence of component 1 exposure to high concentrations of vapor may produce central nervous system depression.

INGESTION: Based on the presence of component 1 product is presumed to be slightly toxic.

SIGNS AND SYMPTOMS: Eye irritation-pain, tearing, reddening and swelling. Skin irritation-swelling, rash and redness. Respiratory irritation- runny nose, sore throat, coughing, chest discomfort, shortness of breath and reduced lung function.

Gastrointestinal irritation-sore throat, abdominal pain, nausea, vomiting and diarrhea.

AGGRAVATED MEDICAL CONDITIONS; Preexisting skin, eye and respiratory disorders may be aggravated by exposure to this product.

OTHER HEALTH EFFECTS: None recognized

Section V-Emergency and First Aid Procedures

EYE CONTACT: Immediately flush eyes with water for at least 15 minutes. Seek medical attention if any symptoms persist.

SKIN CONTACT: Remove contaminated clothing and shoes. Wipe excess from skin and flush with water using soap if available. Seek medical attention if irritation occurs. Do not reuse clothing until thoroughly decontaminated.

INHALATION: Remove victim to fresh air and treat symptomatically. Provide oxygen if breathing is difficult. Give artificial respiration if the victim is not breathing. Seek prompt medical attention.

INGESTION: Dilute with liquid unless the victim is unconscious or very drowsy. If vomiting spontaneously occurs, keep the victim's head below the hips to prevent aspiration into the lungs. Consult a physician, hospital or poison control center and/or transport to an emergency facility immediately.

NOTES FOR PHYSICIAN: The following component-specific information may contain contradictions, and is intentionally included to give the attending physician specific information about the individual components of the blend.

A. Components 1 and 2 may cause severe, permanent damage if aspirated and vomiting should not be induced.

Section VI-Fire and Explosion Hazards

FLASH POINT: >101 Degrees F. TCC

EXTINGUISHING MEDIA: Use water fog, foam, dry chemical or carbon dioxide.

SPECIAL FIRE FIGHTING PROCEDURES AND PRECAUTIONS:

Warning: Combustible. Clear fire area of unprotected personnel. Do not enter confined fire space without helmet, face shield, bunker coat, gloves, rubber boots, and a positive pressure NIOSH-approved self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS: Containers exposed to intense heat from fires should be cooled with water to prevent vapor pressure buildup which could result in container rupture. Containers that are exposed to direct flame should be cooled with water to eliminate structural weakening of the container's wall and possible rupture.

Section VII-Reactivity

STABILITY: Stable

HAZARDOUS POLYMERIZATION: Will not occur

CONDITIONS AND MATERIAL TO AVOID: Based on the presence of components 1 and 2 avoid oxidizing materials.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and unidentified organic compounds may be formed during combustion.

JELL CHEMICALS INC.

Material Safety Data Sheet-Anco EZ100

Report Date 1/19/00

Page 3 of 3

Section VIII-Employee Protection

RESPIRATORY PROTECTION: Use ventilation as required to control vapor concentrations-at least 10 air changes per hour are recommended for good general room ventilation. If exposure exceeds the PEL/TLV, use the appropriate NIOSH-approved respirator.

PROTECTIVE CLOTHING: Wear safety glasses, goggles, or a splash shield to prevent eye contact. Contact lenses should not be worn. Wear appropriate gloves and protective clothing to prevent contact with skin and clothing.

ADDITIONAL PROTECTIVE MEASURES: Eye wash fountains and safety showers should be available for use in an emergency.

Section IX-Environmental Protection

SPILL OR LEAK PROCEDURES:

LARGE SPILLS: Evacuate the hazard area of unprotected personnel. Wear appropriate respirator and protective clothing. Shut off source of leak only if safe to do so. Dike and contain. If vapor cloud forms, water fog may be used to suppress; contain run-off. Remove with vacuum trucks or pump to storage/salvage vessels. Soak up residue with an absorbent such as clay, sand or other suitable material; place in non-leaking containers for proper disposal. Flush area with water to remove trace residue; Flush solutions as above.

SMALL SPILLS: Take up with an absorbent material and place in non-leaking containers; seal tightly for proper disposal.

WASTE DISPOSAL: Observe all federal, state, and local regulations regarding proper disposal.

Section X-Additional Precautions

Keep liquid and vapor away from heat, sparks, and flame. Extinguish pilot lights, cigarettes and turn off other possible sources of ignition prior to use and until vapors are gone. Surfaces that are sufficiently hot may ignite product in the absence of sparks or flame. Vapors may accumulate and travel to ignition sources distant from handling site. Keep containers closed when not in use. Use adequate ventilation. Containers, even if empty, can contain explosive vapors or residues. Do not cut, Drill, Grind, or weld near containers.

After contact with product container, wash with soap and water before eating, drinking, smoking or using toilet facilities.

Under the provisions of Title III, Section 313 of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR, Part 372, the following components may be subject to reporting:

NONE.

THIS INFORMATION RELATES TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. SUCH INFORMATION IS TO THE BEST OF OUR KNOWLEDGE AND BELIEF, ACCURATE AND RELIABLE AS OF THE DATE COMPLIED. HOWEVER, NO REPRESENTATION, WARRANTY OR GUARANTEE IS MADE AS TO ITS ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY HIMSELF AS TO THE SUITABILITY AND COMPLETENESS OF SUCH INFORMATION FOR HIS OWN PARTICULAR USE. WE DO NOT ACCEPT LIABILITY FOR ANY LOSS OR DAMAGE THAT MAY OCCUR FROM THE USE OF THIS INFORMATION.
