

# JELL CHEMICALS, INC.

9353 Seymour Ave. Schiller Park, IL 60176

800/747-5355

## MATERIAL SAFETY DATA SHEET

Report Date: 9/24/99

Page 1 of 4

**EMERGENCY PHONE #: 1-800-535-5053**

### Section I - Product Identification

Product Class: Blend

Product Code I.D.: MS-1841

Trade Name: Anco "L" Dampener Wash

---

---

### Section II A - Hazardous Ingredients

No.	Component	CAS#	% by wt.
1	Tall Oil	(008002-26-4)	5-10
2	Pine Oil	(008002-09-3)	5-10
3	Ethyl Alcohol	(000064-17-6)	1-5
4	Stoddard Solvent	(064742-48-9)	20-25
5	Secondary Alcohol Ethoxylate	(061702-78-1)	1-5
6	Alkanolamide	(000121-40-1)	1-5
7	Sodium Hydroxide Solution	(001310-73-2)	1-5

\*None of the components of this product are recognized as carcinogenic. (NA = Not Applicable)

---

---

### Section II B - Occupational Exposure Limits (Y=Yes, N=No, N/E= Not Established)

No.	(OSHA)PEL/TWA	PEL/CEILING
1	N/E	N/E
2	N/E	N/E
3	1000.000ppm	N/E
4	100.000ppm	N/E
5	N/E	N/E
6	N/E	N/E
7	N/E	2.000mg/m3

---

---

No.	(OSHA)PEL/STEL	Skin*
1	N/E	N
2	N/E	N/E
3	N/E	N
4	N/E	N
5	N/E	N
6	N/E	N
7	N/E	N

---

---

**JELL CHEMICALS INC.**

Material Safety Data Sheet-Anco "L" Dampener Wash

Report Date: 9/24/99

Page 2 of 4

<u>No.</u>	<u>(ACGIH)TLV/TWA</u>	<u>TLV/Ceiling</u>
1	N/E	N/E
2	N/E	N/E
3	1000.000ppm	N/E
4	100.000ppm	N/E
5	N/E	N/E
6	N/E	N/E
7	N/E	2.000mg/m3

---

<u>No.</u>	<u>(ACGIH)TLV/STEL</u>	<u>Skin*</u>
1	N/E	N
2	N/E	N/E
3	N/E	N
4	N/E	N
5	N/E	N
6	N/E	N
7	N/E	N

*\*(Skin) Absorption may contribute to the overall exposure to this material. Take appropriate measures to prevent skin contact..*

---

---

**Section III - Physical Data**

Boiling point: 212 Degrees F (Represents boiling point of lowest boiling material)

Evaporation: <1 (ether=1)

Vapor Density: >1 (air=1)

% solid: 27.78 (theoretical)

Weight per gallon: 7.79 (theoretical)

---

---

**Section IV - Health Information**

EYE CONTACT: Based on the presence of component 7 product is presumed to be corrosive to the eyes. Exposure may cause cause chemical burns and extensive corneal injury. Based on the presence of component 1, 2, 3 and 6 product vapors and/or mists may also be irritating to the eyes.

SKIN CONTACT: Based on the presence of component 7 product is presumed to be corrosive to the skin and exposure may cause chemical burns. Based on the presence of components 3 and 4 prolonged or repeated contact may result in defatting and drying of the skin which may result in dermatitis.

INHALATION: Based on the presence of component 7 product vapors and/or mists are corrosive to the nose, throat, respiratory tract, and other mucous membranes. Overexposure may result in chemical pneumonitis or pulmonary edema which are potentially fatal. Based on the presence of components 3 and 4 exposure to high concentrations of vapor may produce central nervous system depression.

INGESTION: Based on the presence of component 7 product is corrosive and may cause chemical burns to the gastrointestinal tract. Based on the presence of component 4 small amounts of liquid aspirated into the lungs during ingestion or from vomiting may result in severe lung damage. Based on the presence of component 3 ingestion may cause central nervous system depression.

SIGNS AND SYMPTOMS: Eye irritation-pain, tearing, reddening and swelling. Skin irritation-swelling, rash and redness. Respiratory irritation- runny nose, sore throat, coughing, chest discomfort, shortness of breath and reduced lung function. Gastrointestinal irritation-sore throat, abdominal pain, nausea, vomiting and diarrhea. Based on the presence of component 3 central nervous system depression-headache, dizziness, nausea and symptoms of intoxication; In extreme cases, unconsciousness and death may occur. Chronic overexposure-loss of memory, loss of intellectual ability and loss of coordination.

**JELL CHEMICALS INC.**

Material Safety Data Sheet-Anco "L" Dampener Wash

Report Date 9/24/99

Page 3 of 4

AGGRAVATED MEDICAL CONDITIONS; Preexisting skin, eye and respiratory disorders may be aggravated by exposure to this product. Impaired central nervous system functions from preexisting disorders may be aggravated by exposure to this product.

OTHER HEALTH EFFECTS: Based on the presence of component 4 chronic overexposure may cause damage to the kidneys. Based on the presence of component 5 chronic overexposure may cause damage to the lungs.

---

---

**Section V-Emergency and First Aid Procedures**

EYE CONTACT: Immediately flush eyes with copious amounts of water for at least 15 minutes while holding eyelids open. Seek prompt medical attention.

SKIN CONTACT: Immediately remove contaminated clothing and shoes. Wipe excess from skin and flush with water for at least 15 minutes using soap if available. Seek prompt medical attention. Do not reuse clothing until thoroughly decontaminated.

INHALATION: Remove victim to fresh air and treat symptomatically. Provide oxygen if breathing is difficult. Give artificial respiration if the victim is not breathing. Seek prompt medical attention.

INGESTION: Do not induce vomiting. Vomiting will cause further damage to the throat. Dilute by giving water or milk to drink if the victim is conscious. Consult a physician, hospital or poison control center and/or transport to an emergency facility immediately.

NOTES FOR PHYSICIAN: The following component-specific information may contain contradictions, and is intentionally included to give the attending physician specific information about the individual components of the blend.

A. Components 4, 5 and 7 may cause severe, permanent damage if aspirated and vomiting should not be induced.

---

---

**Section VI-Fire and Explosion Hazards**

FLASH POINT: >100 Degrees F. TCC

EXTINGUISHING MEDIA: Use water fog, foam, dry chemical or carbon dioxide.

SPECIAL FIRE FIGHTING PROCEDURES AND PRECAUTIONS:

Warning: Combustible. Clear fire area of unprotected personnel. Do not enter confined fire space without helmet, face shield, bunker coat, gloves, rubber boots, and a positive pressure NIOSH-approved self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS: Containers exposed to intense heat from fires should be cooled with water to prevent vapor pressure buildup which could result in container rupture. Containers that are exposed to direct flame should be cooled with water to eliminate structural weakening of the container's wall and possible rupture.

---

---

**Section VII-Reactivity**

STABILITY: Stable

HAZARDOUS POLYMERIZATION: Will not occur

CONDITIONS AND MATERIAL TO AVOID: Based on the presence of components 1, 2, 4, 5 and 6 avoid oxidizing materials. Based on the presence of component 5 avoid strong acids, alkalies at high temperature. Based on the presence of component 6 avoid lead, copper, and their alloys. Based on the presence of components 6 and 7 avoid aluminum and its alloys. Based on the presence of component 7 avoid contact with zinc, amines, polyamines, and polyamides under uncontrolled conditions. Based on the presence of component 4 avoid chlorinated compounds. Based on the presence of component 7 avoid brass. Based on the presence of component 6 do not use with nitrosating agents. Since nitrosamines may form, some nitrosamines have been shown to be carcinogenic in lab tests.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides and compounds of nitrogen, carbon dioxide, carbon monoxide and unidentified organic compounds may be formed during combustion.

---

---

**JELL CHEMICALS INC.**

Material Safety Data Sheet-Anco "L" Dampener Wash

Report Date 8/27/99

Page 4 of 4

**Section VIII-Employee Protection**

RESPIRATORY PROTECTION: Use ventilation as required to control vapor concentrations-at least 10 air changes per hour are recommended for good general room ventilation. If exposure exceeds the PEL/TLV, use the appropriate NIOSH-approved respirator.

PROTECTIVE CLOTHING: Wear safety glasses, goggles, or a splash shield to prevent eye contact. Contact lenses should not be worn. Wear appropriate gloves and protective clothing to prevent contact with skin and clothing.

ADDITIONAL PROTECTIVE MEASURES: Eye wash fountains and safety showers should be available for use in an emergency.

---

---

**Section IX-Environmental Protection**

SPILL OR LEAK PROCEDURES:

LARGE SPILLS: Evacuate the hazard area of unprotected personnel. Wear appropriate respirator and protective clothing. Shut off source of leak only if safe to do so. Dike and contain. If vapor cloud forms, water fog may be used to suppress; contain run-off. Remove with vacuum trucks or pump to storage/salvage vessels. Soak up residue with an absorbent such as clay, sand or other suitable material; place in non-leaking containers for proper disposal. Flush area with water to remove trace residue; Flush solutions as above.

SMALL SPILLS: Take up with an absorbent material and place in non-leaking containers; seal tightly for proper disposal.

WASTE DISPOSAL: Observe all federal, state, and local regulations regarding proper disposal.

---

---

**Section X-Additional Precautions**

Keep liquid and vapor away from heat, sparks, and flame. Extinguish pilot lights, cigarettes and turn off other possible sources of ignition prior to use and until vapors are gone. Surfaces that are sufficiently hot may ignite product in the absence of sparks or flame. Vapors may accumulate and travel to ignition sources distant from handling site. Keep containers closed when not in use. Use adequate ventilation. Containers, even if empty, can contain explosive vapors or residues. Do not cut, Drill, Grind, or weld near containers.

After contact with product container, wash with soap and water before eating, drinking, smoking or using toilet facilities.

Under the provisions of Title III, Section 313 of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR, Part 372, the following components may be subject to reporting:

Secondary Alcohol Ethoxylate (CAS# 061702-78-1) 3.32 Wt%

---

---

**THIS INFORMATION RELATES TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. SUCH INFORMATION IS TO THE BEST OF OUR KNOWLEDGE AND BELIEF, ACCURATE AND RELIABLE AS OF THE DATE COMPLIED. HOWEVER, NO REPRESENTATION, WARRANTY OR GUARANTEE IS MADE AS TO ITS ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY HIMSELF AS TO THE SUITABILITY AND COMPLETENESS OF SUCH INFORMATION FOR HIS OWN PARTICULAR USE. WE DO NOT ACCEPT LIABILITY FOR ANY LOSS OR DAMAGE THAT MAY OCCUR FROM THE USE OF THIS INFORMATION.**

---

---